

Magnetic

Magnetic Bridle Ring



Strong, fast and cost-effective alternative cable management solution for network cable pathway applications









- Exceptional strength neodymium rare earth magnet provides a secure hold onto any ferromagnetic surface
- Ring crafted from cold-rolled, low-carbon steel enhancing wear resistance
- Quick & easy to install without specialized tools and equipment
- Short standoff brings the bridle ring closer to the magnet making for a stronger hold
- Protective steel cup directs magnetic field to fastening surface increasing magnetic pull force
- Sticks through oil, grease, and dirty areas
- Magnets will not interfere with ethernet or wi-fi signals
- Cost effective alternative to expensive cable tray
- Provides support for CAT5e/CAT6 category cable, lowvoltage wire, coax, signal & control cable and electrical wire up to 600V
- Suitable for use in air handling systems (plenums) in accordance with Section 300.22 (C) and (D) of the National Electric Code
- **UL & CUL listed**

Application:

- Provides support in the distribution of wire & cable bundles
 - Network/Data
 - Telcom/Voice
 - Broadband, Satellite, CCTV
 - Low Voltage/Security/Fire Alarm
 - Signal/Control Cable
 - **Electrical Wire**

Installation:

- Secures to steel beams, ceiling decks, sheet metal, metal joists & other ferromagnetic surfaces
- Use for horizontal or vertical cable runs





Magnetic

Part Numbers

Part #	Description	Box Qty	12-digit UPC
WBR075MAG	3/4" Magnetic Bridle Ring, 26 lb Magnet, Short Stem	100	811443030581
WBR075MAG-10	3/4" Magnetic Bridle Ring, 26 lb Magnet, Short Stem, Retail Bag, 10 Pk	10	811443033070
WBR075MAGBK	3/4" Magnetic Bridle Ring, 26 lb Magnet, Short Stem, Black	100	811443031397
WBR075MAGBK-10	3/4" Magnetic Bridle Ring, 26 lb Magnet, Short Stem, Black, Retail Bag, 10 Pk	10	811443033117

|Permanent fixation but still provides the flexibility to be repositioned where needed|

|Can be used on walls and ceilings, making them ideal for multi-directional cable runs|

| Designed with an open loop for easy cable installation |

Extremely strong, versatile, reliable, and durable in a slim profile design

|No tools needed, simply attach the magnet to a metal surface and run cables|

If using a bridle ring with high performance data cable a saddle is required to ensure proper bend

|Non-continuous supports may not exceed spacing of 5' per TIA 569-C.9.7|

Related Items

Part #	Description		
WBR125MAG	1-1/4" Magnetic Bridle Ring, 100 lb Magnet, Short Stem		
WBR200MAG	2" Magnetic Bridle Ring, 100 lb Magnet, Short Stem		
WBR200SDLMAG	2" Magnetic Bridle Ring, 100 lb Magnet, Saddle		
WMAG26HK	26 lb Magnetic Mini Hook		
075GRIPTAPE	.75" Self-Gripping Tape (Hook & Loop), 75 Ft Roll, Black		
WMAG26	26 lb Counterbored Mounting Pot Magnet		





Specify Winnie...

- ✓ Since 2015
- Family-Owned & Operated

Consult & follow local codes and practices

Personal & Friendly Customer Service

Magnet Specifications:

Size: 23.2mm x 4.5mm Mounting Hole: 5mm

Grade: N45M

Magnet Plating: NdFeB

Temperature Tolerance: -40°F - 212°F (-40°C - 100°C)

Cup: Nickel-plated steel

Black powder-coated steel

Safety:

- Please handle neodymium magnets with care
- Keep neodymium magnets away from anyone with a pacemaker
- Magnets are not toys and should be kept away from children and pets
- Large powerful magnets can pinch your fingers or cause other injuries, use caution

© Winnie Industries, LLC. All Rights Reserved. Drawings are proprietary and may not be copied or used without express written permission.

Rev 202406







