

J Hook



J Hook with 90° Angle Clip & Spring Steel Beam Clamp, 360° Rotation

Cable management solutions for data centers, connected buildings and other commercial network cable pathway applications

Features:

- Pre-assembled with spring steel beam clamp
- Time saving and cost-effective alternative compared to using mesh cable basket or ladder tray
- Heavy duty pre-galvanized steel
- Smooth rounded edges for the proper bend radius of cables
- For all types of category cable, low-voltage wire, coax, innerduct and flexible conduit & tubing
- Provides excellent support for CAT5e, CAT6, CAT6A, CAT7 and fiber optic cables
- ¼" x 20 threaded hole tapped on side
- 3/8" through hole on the top and bottom
- Supplied with an installed 14-20 x 1" combination Philips/slotted hex head machine screw
- 360° swivel for flexible installation
- Serrated jaws for additional gripping power
- Includes wire cable retainer clip*
- **UL & CUL listed**
- Complies with NEC® and TIA/EIA requirements for structured cabling systems

Application:

- Provides support in the distribution of wire & cable bundles
 - Telcom/Voice
 - Network/Data
 - Fiber
 - Broadband, Satellite, CCTV
 - Low Voltage/Security
 - Flexible Conduit

Installation:

- Attaches to beam flange up to 1/2" thick
- Secure with the included bolt using a socket driver or Philips head screwdriver





*WJH12xx uses bendable tab for securing wires



WJH96 is not UL listed

engineered and manufactured to make installs easier





J Hook

Part Numbers

| Part # | Description | Box Qty | 12-digit UPC |
|-------------|--|----------------|--------------|
| WJH12ACSSBC | 3/4" J Hook, 90° Angle Clip, Spring Steel Beam Clamp, 360° Rotation | 100 | 811443030109 |
| WJH21ACSSBC | 1 5/16" J Hook, 90° Angle Clip, Spring Steel Beam Clamp, 360° Rotation | 100 | 811443030222 |
| WJH32ACSSBC | 2" J Hook, 90° Angle Clip, Spring Steel Beam Clamp, 360° Rotation | 100 | 811443030345 |
| WJH64ACSSBC | 4" J Hook, 90° Angle Clip, Spring Steel Beam Clamp, 360° Rotation | 25 | 811443030468 |
| WJH96ACSSBC | 6" J Hook, 90° Angle Clip, Spring Steel Beam Clamp, 360° Rotation | 25 | 811443031434 |

|Fully versatile J Hook solution with 14 interchangeable fasteners and support brackets|

|Ready to use out of the box, saving installation time and labor|

|Available in multiple color options to aid in the identification and organization of the pathway application|
|Non-continuous supports may not exceed spacing of 5' per TIA 569-C.9.7|

Cable Capacity

| Part Number | Hook Size | Area (sq in) | Cat 5e | Cat 6 | Cat 6A | Cat 7 ScTP/FTP | RG59 | RG6 |
|-------------------------|-----------|--------------|--------|-------|--------|-------------------|------|-----|
| Cable Diameter (inches) | | | 0.19 | 0.24 | 0.3 | 0.33 | 0.24 | 0.3 |
| WJH12* | 3/4" | 0.6 | 16 | 10 | 6 | 5 | 9 | 8 |
| WJH21* | 1 5/16" | 2.16 | 53 | 33 | 20 | 18 | 33 | 28 |
| WJH32* | 2" | 3.17 | 80 | 50 | 34 | 26 | 48 | 42 |
| WJH64* | 4" | 15.28 | 370 | 230 | 150 | 125 | 235 | 200 |
| WJH96* | 6" | | 370 | 230 | 150 | 125 | | |



Cable capacity is based on 70% fill
Consult & follow local codes and practices

Category cable outside diameter varies by type and manufacturer; consult with cable manufacturer to ensure proper cable outside diameter is being used for calculations

Related Items

| Part # | Description |
|-------------|---|
| WSSBC | Spring Steel Beam Clamp, 1/8"-1/2" Flange |
| 075GRIPTAPE | 3/4" Grip Tape, 75ft, Black |



We understand that not all projects can be fulfilled with offthe-shelf products which is why our Quick Build program can deliver j hook trees or other custom configurations FAST!!

Specify Winnie...

- ✓ Since 2015
- √ Family-Owned & Operated
- ✓ Personal & Friendly Customer Service





All WJH21, WJH32, WJH64 styles include retaining clips. WJH12 has a bendable tab.



All J Hooks are easily customized with 14 different fasteners and support brackets for any application.

© Winnie Industries, LLC. All Rights Reserved. Drawings are proprietary and may not be copied or used without express written permission.

Rev 202403

