

Magnetic



Extremely strong, versatile, reliable, durable and cost-effective solution for holding, mounting and positioning on THIN metal



- Permanent nine-pole charged rare earth neodymium magnet
- Exceptionally strong when compared to conventional neodymium pot magnets
- Vertical pull force up to 150 lb on sheet metal
- Due to the intense magnetic attraction at the surface, will not easily slide like other magnets
- Black epoxy coating provides corrosion resistance
- Powerful grip packed into a thin profile
- · Sticks through oil, grease and dirty areas
- Provides the flexibility of being permanent or repositionable
- ¼-20 threading enables the attachment of a wide variety of brackets, hooks and other holding attachments
- Screw stopping feature
- Long-lasting performance in a variety of demanding indoor and outdoor conditions

Application:

• Secure temporary lights, signs, fixtures, hardware tools, etc

Installation:

- Secures to steel beams, ceiling decks, sheet metal, metal joists, van walls & other ferromagnetic surfaces
- Engineered for max attachment to thin metal

Specifications:

- Size: 2" x 3/8" (50.8mm x 9.5mm)
- Threaded Hole: ¼ x 20
- Vertical Pull Force: 150 lb
- Coating: Epoxy
- Material: Magnet: Neodymium (NdFeB)
 - Fender Washer: Steel
- Temperature Tolerance: -40°F 176°F (-40°C 80°C)



Nothing else on the Market Compares



Magnetic

Part Numbers

| Part # | Description | Box Qty | 12-digit UPC |
|-----------------|----------------------------------------------------------|---------|--------------|
| WUMAG-1420UHD | 150lb Ultra Heavy-Duty Mounting Magnet, UHD | 100 | 811443033230 |
| WUMAG-1420UHD-5 | 150lb Ultra Heavy-Duty Mounting Magnet, UHD, Retail, 5pk | 10 | 811443032912 |

|Suitable for all indoor and outdoor holding and fastening applications| |Ideal for holding workpieces, securing tools or positioning equipment with flexibility and ease| | Engineered to hold to ferromagnetic surfaces thinner than 1mm|

| Epoxy coating provides outstanding chemical resistance, durability, and toughness |

|Corrosion resistant makes them ideal for outdoor or marine environment|

|Hundreds of uses in sporting, household, industrial and commercial applications|

|Completely hide from view, making them ideal for applications where aesthetics is important|



Uses

| Applications | | | |
|----------------------------------|-----------------------------|--|--|
| Marine | Agricultural Industry | | |
| Car Lifts | Routing Conduit | | |
| Trailer & Car Frames | Routing Low Voltage Wire | | |
| Retail Signs | Holding Tools to Work Bench | | |
| Warehousing & Forklifts | Holding Temporary Wiring | | |
| Holding Sensor Wiring on Tooling | Healthcare | | |
| Securing Hydraulic Lines | Stage, Theater & Concerts | | |
| Automation Robotics | Solar Steel Structures | | |
| Transportation Industry | Wind Turbines | | |
| Renewable Energy | Oil & Gas Rigs | | |
| Hydrogen Fuel Facilities | Arts & Crafts | | |
| Bulk Tanks & Storage Silos | And Much More | | |

| | Use With | |
|-----------------------|-------------------|---------------------------|
| Plenum Ceilings | Electrical Boxes | Communication Towers |
| Access Control Panels | Enclosures | Building Service Entrance |
| Bar Joists | Wire Baskets | Ceiling Deck Pans |
| Walk In Coolers | Strut Channels | Raised Floors |
| Walk In Freezers | Inside Panels | Cable Trays |
| Drop Ceiling Grid | Outside Panels | Steel Beams |
| Pallet Racks | Machinery/Presses | Metal Studs |
| Data Racks | Data Cabinets | Sprinkler Pipes |

Nothing else on the Market Compares

Specify Winnie...

- ✓ Since 2015
- √ Family-Owned & Operated
- ✓ Personal & Friendly Customer Service
- + Please handle neodymium magnets with care
- + Keep neodymium magnets away from anyone with a pacemaker
- + Magnets are not toys and should be kept away from children and pets
- + Large powerful magnets can pinch your fingers or cause other injuries, use caution



© Winnie Industries, LLC. All Rights Reserved. Drawings are proprietary and may not be copied or used without express written permission.

Rev 202403

