



Winnie Industries

MANUFACTURER OF FASTENING SUPPORTS

Magnetic

Ultra Heavy-Duty Mounting Magnet with Bridle Ring & Saddle

**Extremely strong, fast, and cost-effective cable management solution
for mounting on THIN metal**



Features:

- Permanent nine-pole charged rare earth neodymium magnet
- Exceptionally strong when compared to conventional neodymium pot magnets
- Vertical pull force up to 150 lb on sheet metal
- Due to the intense magnetic attraction at the surface, will not easily slide like other magnets
- Magnet's black epoxy coating provides corrosion resistance
- Bridle ring is crafted from heavy-duty, zinc plated steel
- Available in 2" and 4" ring diameter
- Plenum-rated saddle provide optimal bending radius and support for data cable bundles
- Designed for sensitive fiber optic and data cabling ensuring proper cable bend
- Provides support for CAT5e, CAT6, CAT6A, CAT7, low-voltage and fiber optic cables
- Sticks through oil, grease and dirty areas
- Long-lasting performance in a variety of demanding conditions
- Suitable for use in air handling systems (plenums) in accordance with Section 300.22 (C) and (D) of the National Electric Code



Application:

- Provides support in the distribution of wire and cable bundles
 - Telecom/Voice
 - Network/Data
 - Broadband, Satellite, CCTV
 - Low Voltage/Security
 - Fiber

Installation:

- Secures to steel beams, ceiling decks, sheet metal, metal joists, van walls & other ferromagnetic surfaces
- **Engineered for max attachment to thin metal**

Plenum
RATED

engineered and manufactured to make installs easier

winnieindustries.com



5420 Newport Dr. Unit 62
Rolling Meadows, IL 60008

224-993-0011
sales@winnieindustries.com



Magnetic

Part Numbers

Part #	Description	Box Qty	12-digit UPC
WUMAG-WBR4T200SDL	2" Bridle Ring, 1.5" Stem, 150 lb Magnet, Saddle	10	811443033674
WUMAG-WBR200SHORTSDL	2" Bridle Ring, Short Stem, 150 lb Magnet, Saddle	10	811443033650
WUMAG-WBR4T400SDL	4" Bridle Ring, 1.5" Stem, 150 lb Magnet, Saddle	10	811443033667

- | Reduces job labor costs on permanent or temporary installations |
- | Provides great support, eliminating stress, and following the natural curves and bends of cable |
- | Engineered to hold to ferromagnetic surfaces thinner than 1mm |
- | Magnet epoxy coating provides outstanding chemical resistance, durability, and toughness |
- | Fast and cost-effective solution to support data, voice, security, and video cable |
- | If using a bridle ring with high performance data cable a saddle is required to ensure proper bend |
- | Non-continuous supports may not exceed spacing of 5' per TIA 569-C.9.7 |



Related Items

Part #	Description
075GRIPTAPE	3/4" Grip Tape, 75ft, Black
WUMAG-1420UHD	150 Lb Ultra Heavy-Duty Mounting Magnet, UHD

Nothing else on the Market Compares

Magnet Specifications:

- Size: 2" x 3/8" (50.8mm x 9.5mm)
- Threaded Hole: 1/4 x 20
- Vertical Pull Force: 150 lb
- Coating: Epoxy
- Material: Magnet: Neodymium (NdFeB)
Fender Washer: Steel
- Temperature Tolerance: -40°F - 176°F (-40°C - 80°C)

Specify Winnie...

- ✓ Since 2015
- ✓ Family-Owned & Operated
- ✓ Personal & Friendly Customer Service

- + Please handle neodymium magnets with care
- + Keep neodymium magnets away from anyone with a pacemaker
- + Magnets are not toys and should be kept away from children and pets
- + Large powerful magnets can pinch your fingers or cause other injuries, use caution

