



Winnie Industries

MANUFACTURER OF FASTENING SUPPORTS

Magnetic

Ultra Heavy-Duty Mounting Magnet with J Hook for Overhead Mount

**Extremely strong, fast, and cost-effective cable management solution
for mounting on THIN metal**



Features:

- Permanent nine-pole charged rare earth neodymium magnet
- Exceptionally strong when compared to conventional neodymium pot magnets
- Vertical pull force up to 150 lb on sheet metal
- Due to the intense magnetic attraction at the surface, will not easily slide like other magnets
- Sticks through oil, grease and dirty areas
- Magnet's black epoxy coating provides corrosion resistance
- J Hook is crafted from heavy-duty pre-galvanized steel
- Smooth rounded edges for the proper bend radius of cables
- For all types of category cable, low-voltage wire, coax, innerduct and flexible conduit & tubing
- Provides excellent support for CAT5e, CAT6, CAT6A, CAT7 and fiber optic cables
- Includes wire cable retainer clip*
- Complies with NEC® and TIA/EIA requirements for structured cabling systems

Application:

- Provides support in the distribution of wire and cable bundles
 - Telcom/Voice
 - Network/Data
 - Fiber
 - Broadband, Satellite, CCTV
 - Low Voltage/Security
 - Flexible Conduit

Installation:

- Secures to steel beams, ceiling decks, sheet metal, metal joists, van walls & other ferromagnetic surfaces
- **Engineered for max attachment to thin metal**

*WJH12xx uses bendable tab for securing wires



engineered and manufactured to make installs easier

winnieindustries.com



5420 Newport Dr. Unit 62
Rolling Meadows, IL 60008

224-993-0011
sales@winnieindustries.com



Winnie Industries

MANUFACTURER OF FASTENING SUPPORTS

Magnetic

Part Numbers

Part #	Description	Box Qty	12-digit UPC
WUMAG-WJH12AC	3/4" J Hook, 150 lb Magnet, Overhead Mount, UHD	100	811443033612
WUMAG-WJH21AC	1 5/16" J Hook, 150 lb Magnet, Overhead Mount, UHD	100	811443033629
WUMAG-WJH32AC	2" J Hook, 150 lb Magnet, Overhead Mount, UHD	100	811443033636
WUMAG-WJH64AC	4" J Hook, 150 lb Magnet, Overhead Mount, UHD	25	811443033643
WUMAG-WJH96AC	6" J Hook, 150 lb Magnet, Overhead Mount, UHD	25	811443033940

- | Ready to use out of the box, saving installation time and labor on permanent or temporary installations|
- | Engineered to hold to ferromagnetic surfaces thinner than 1mm |
- | Time saving and cost-effective alternative compared to using mesh cable basket or ladder tray|
- | Epoxy coating on magnet provides outstanding chemical resistance, durability, and toughness|
- | Non-continuous supports may not exceed spacing of 5' per TIA 569-C.9.7|



Cable Capacity

Part Number	Hook Size	Area (sq in)	Cat 5e	Cat 6	Cat 6A	Cat 7 ScTP/FTP	RG59	RG6
Cable Diameter (inches)			0.19	0.24	0.3	0.33	0.24	0.3
WJH12*	3/4"	0.6	16	10	6	5	9	8
WJH21*	1 5/16"	2.16	53	33	20	18	33	28
WJH32*	2"	3.17	80	50	34	26	48	42
WJH64*	4"	15.28	370	230	150	125	235	200

Cable capacity is based on 70% fill
 Consult & follow local codes and practices
 Category cable outside diameter varies by type and manufacturer; consult with cable manufacturer to ensure proper cable outside diameter is being used for calculations

Related Items

Part #	Description
075GRIPTAPE	3/4" Grip Tape, 75ft, Black
WUMAG-1420UHD	150 Lb Ultra Heavy-Duty Mounting Magnet, UHD



We understand that not all projects can be fulfilled with off-the-shelf products which is why our Quick Build program can deliver j hook trees or other custom configurations **FAST!!**

Specify Winnie...

- ✓ Since 2015
- ✓ Family-Owned & Operated
- ✓ Personal & Friendly Customer Service

Safety:

- + Please handle neodymium magnets with care
- + Keep neodymium magnets away from anyone with a pacemaker
- + Magnets are not toys and should be kept away from children and pets
- + Large powerful magnets can pinch your fingers or cause other injuries, use caution

Magnet Specifications:

- Size: 2" x 3/8" (50.8mm x 9.5mm)
- Threaded Hole: 1/4 x 20
- Vertical Pull Force: 150 lb
- Coating: Epoxy
- Material: Magnet: Neodymium (NdFeB)
Fender Washer: Steel
- Temperature Tolerance: -40°F - 176°F (-40°C - 80°C)



Consult & follow local codes and practices

© Winnie Industries, LLC. All Rights Reserved. Drawings are proprietary and may not be copied or used without express written permission.

Rev 202404

engineered and manufactured to make installs easier

winnieindustries.com



5420 Newport Dr. Unit 62
Rolling Meadows, IL 60008

224-993-0011
sales@winnieindustries.com